PRODUCT SPECIFICATION GUIDE NEILPRYDE PERFORMANCE ROLLER FURLING GENOA Standard Features ٠ Radial layout allows "step-down" construction providing a reefable headsail in a variety of composite cruising fabrics ٠ Corner rings are webbed stainless steel external rings with leather chafe patches or doubled webbing straps for furling flexability ٠ All seams will have 1 to 3 rows of 3-step stitching, depending on size ٠ Patches Fan/Radial type with buffers along foot and leech. ٠ Sails include draft stripe Polyester or Spectra leech & foot lines Tell-tails and one tell tail window The Neil Pryde Foam ٠ Heavy Duty sailbag System. 2 or 3 rows of contrasting 3step stitching and internal leechline chafe guard **Optional Features** ٠ U.V. sacrificial cover either in Acrilon or light weight u.v. polyester Multi-Track Foam Luff System Seamkote **Tradewinds Specifications** Sail numbers

Up and Over Leechline



Strapped-in rings for ultimate durability.

Integrated reefing patch along foot and leech (at head) and reefing marks to match pre-configured sheet lead locations.

## Quality, Service, Value

- Performance Cruise sails come with the assurance of a two year warranty of quality, service and value.
- If you ever need service, our consultants will direct you to the nearest of our worldwide network of Service lofts.
- No matter where in the world your sailing takes you, we are there to help.
- For further information, contact your Neil Pryde consultant by dialing 1-203-874-6984 or http://www.neilprydesails.com

Copyright Neil Pryde Sails Int. 2002 19-Oct-01 Drawings and type may describe features not applicable to all sizes of sails. Our ongoing development program may change features and specifications without notice.